

INTRODUCING THE NEW GENERATION

The lightweight Easipower Plus has been designed to deliver 15% more power than the original model, and now comes supplied with soft grip overmouldings to improve operator comfort and tool support on inclined surfaces. It is suitable for use with low to medium viscosity materials and will cope easily with a wide range of cartridge and sachet systems.

Well-balanced and easy to use, Easipower Plus is designed and manufactured in the UK by PC Cox, the world's leading manufacturer of sealant and adhesive applicators.

EasipowerPlus[™]



COX FOR QUALITY APPLICATORS

The latest generation of Cox Easipower Plus dispensers provides the ideal portable tool for the semi-professional user. Manufactured in the UK to strict ISO standards, Easipower Plus sets the benchmark for reliable battery-powered applicators which are easy-to-use, lightweight and ergonomically designed. Its sophisticated electronic control system delivers material in a smooth and precise manner. The speed sensitive trigger switch also enables less experienced operators to produce consistent beads of material on a repeated basis.

PRODUCT APPROVALS

The Easipower Plus dispensers have all been extensively tested to ensure that they meet all the latest CE requirements. The batteries are fully UN compliant and the battery chargers are IEC60335 and UL approved.

EasipowerPlus[™]

The lightweight cordless solution

Latest Li-Ion Battery Technology

- Rechargeable 10.8V lithium-ion battery
- Fully charged within 30 minutes of using a universal charger
- · High energy densities
- No memory loss -can be charged at any time (doesn't have to be run empty first)
- Considerably less loss of charge when not in use (charge still in place even after months of limited use)
- All applicators are supplied with ONE battery as standard; a second battery can be supplied on request at an additional cost









RANGE FEATURES

- Variable speed control for easy management of material flow
- Non-drip auto reverse function: rack will pull back automatically when the trigger is released preventing material overflow
- · Lightweight and comfortable to use
- · Overload shut off to prevent damage to parts and electronics when overloaded

Easipower Plus Cartridge



EasipowerPlus[®]

- · Low medium viscosity
- · Metal frame with support straps to secure cartridge in place
- · Reinforced front plate for extra stability
- · Maximum (no load) speed: 9mm/sec











1.5Ah



1.63kg

For 400ml Cartridges

For US Quart Cartridges



- · Low viscosity
- · Metal frame
- · NON-reinforced front plate (for low viscosity ONLY)
- Maximum (no load) speed: 9mm/sec











1.63kg

1.5Ah

Metal frame

• NON-reinforced front plate (for low viscosity ONLY)

· Maximum (no load) speed: 9mm/sec



· Low viscosity









10.8v 1.5Ah (US QUART)

946ml

2.5kN

1.95kg

Easipower Plus Combi for Sachets AND Cartridges





Easipower Plus

- Low medium viscosity Light aluminium barrel
- Most versatile tool for cartridges AND sachets
- · Maximum (no load) speed 9mm/sec











10.8v 310ml 1.5Ah 400ml 400ml

310ml 2.5kN 1.65kg **1.7kg**

600ml 1.86kg

Easipower Plus Coaxial



EasipowerPlus

- · Low medium viscosity · Light aluminium barrel
- 2-component coaxial cartridge
- · Maximum (no load) speed 9mm/sec













380ml 1.5Ah

1.82kg

EasipowerPlus standard accessories



Battery

(1 supplied as standard) PART NUMBER: 7E1651



COX Accessories

A wide range of accessories are available for you to get the most from your applicator



Bespoke power and viscosity options

For different power or viscosity requirements, please contact us or visit www.pccox.co.uk

PRODUCT RANGE BY POWER

Easiflow"

Airflow 3™

Powerflow[™]

EasipowerPlus

Ultraflow™























World leading consumer support

Cox have a library of online tutorial videos which offer support and training, enabling you to use our products to the best of your ability.

www.pccox.co.uk/academy



PC Cox Ltd., Turnpike Road, Newbury, Berkshire, RG14 2LR T Sales +44 (0) 1635 264500 F +44 (0) 1635 264555 E sales@pccox.co.uk www.pccox.co.uk

Every effort has been made to ensure that the information contained in this leaflet was correct at the time of going to press. However, the company retains the right to change any specification without notice, in line with the company's policy of continual product development.







